Pbmtoppa User Manual

pbmtoppa

Updated: 01 May 2000
Table Of Contents

NAME

pbmtoppa - convert PBM image to HP Printer Performance Architecture (PPA)

SYNOPSIS

pbmtoppa [*pbm_file* [*ppa_file*]]

DESCRIPTION

This program is part of Netpbm. **pbmtoppa** converts page images in PBM format to Hewlett Packard's PPA (Printer Performance Architecture) format, which is the data stream format expected by some HP "Windows-only" printers including the HP Deskjet 820C series, the HP DeskJet 720 series, and the HP DeskJet 1000 series.

pbm_file is the file specification of the input file or **-** for Standard Input. The default is Standard Input.

The input file contains one or more PBM images, with each one being a single page. Each image must have the exact dimensions of a page (at 600 pixels per inch in both directions). Significantly, this is the format that Ghostscript produces.

ppa_file is the file specification of the output file or **-** for Standard Output. The default is Standard Output.

To print Postscript on an HP PPA printer, just use Ghostscript with the **pbmraw** (or **pbm**) device driver.

You can generate a test page for use with this program with **pbmpage**.

You can also set up a printer filter so you can submit PBM input directly to your print queue. See the documentation for your print spooler for information on how to do that, or look in hp820install.doc for an example lpd print filter for Postscript and text files.

Sometimes, **pbmtoppa** generates a file which the printer will not print (because **pbmtoppa**'s input is unprintable). When this happens, all three lights blink to signal the error. This is usually because there is material outside of the printer's printable area. To make the file print, increase the margins via **pbmtoppa** options or a configuration file. See the section on calibration below.

OPTIONS

-v *version*printer version (720, 820, or 1000)

-x *xoff*horizontal offset adjustment in 1/600 inches.

-y *yoff*vertical offset adjustment in 1/600 inches.

-t *topmarg*top margin in 1/600 inches (default: 150 = 0.25 inch)

-l *leftmarg*left margin in 1/600 inches (default: 150 = 0.25 inch)

-r *rightmarg*right margin in 1/600 inches (default: 150 = 0.25 inch)

-b *botmarg*bottom margin in 1/600 inches (default: 150 = 0.25 inch)

-s *paper*paper size: **us** or **a4**. Default is **us**.

-d *dpi*Print resolution in dots per inch.

-f *cfgfile*Read parameters from the configuration file named *cfgfile*. See CONFIGURATION FILES

The offset adjustments you specify with **-x** and **-y** accumulate. I.e. if you specify them multiple times, the total offset adjustment is the sum of the adjustments you specify. **-x 60 -x 120** is the same as **-x 180**.

The **-v** option undoes any preceding **-x** and **-y** options, leaving the horizontal and vertical adjustments their default values.

CONFIGURATION FILES

You can use a configuration file to specify parameters rather than use invocation options. **pbmtoppa** processes the file **/etc/pbmtoppa.conf**, if it exists, before processing any options. It then processes each configuration file named by a **-f** option in order, applying the parameters from the configuration file as if they were invocation options used in the place of the **-f** option.

Configuration files have the following format:

#*Comment*
key1 value1
key2 value2
[etc.]

Valid *key*s are **version**, **xoffset**, **yoffset**, **topmargin**, **leftmargin**, **rightmargin**, **bottommargin**, **papersize**, or any non-null prefix of these words. Valid values are the same as with the corresponding invocation parameters.

EXAMPLES

Print a test pattern:

pbmpage | pbmppa >/dev/lp1

Print three pages:

cat page1.pbm page2.pbm page3.pbm | pbmppa >/dev/lp1

Print the Postscript file myfile.ps:

gs -sDEVICE=rawpbm -q -dNOPAUSE -r600 -sOutputFile=- myfile.ps ;| pbmtoppa | lpr

CALIBRATION

To be able to print successfully and properly, you need to tell **pbmtoppa** an X and a Y offset appropriate for your printer to use when generating the page. You can specify these offsets with the **-x** and **-y** invocation options or with the **xoff** and **yoff** parameters in a **pbmtoppa** configuration file.

To determine the correct offsets, use the **pbmpage** program.

If while trying to do this calibration, the printer refuses to print a page, but just blinks all three lights, specify large margins (e.g. 600 pixels -- one inch) via **pbmpage** invocation options while doing the calibration.

For example:

pbmpage | pbmtoppa >/dev/lp1

or

pbmpage | pbmtoppa | lpr -l

(if your printer filter recognizes the '-l' (direct output) parameter).

In the test pattern, the grid is marked off in pixel coordinate numbers. Unfortunately, these coordinates are probably cut off before the edge of the paper. You'll have to use a ruler to estimate the pixel coordinate of

the left and top edges of the actual sheet of paper (should be within +/- 300, may be negative; there are 600 pixels per inch).

Add these coordinates to the X and Y offsets by either editing the configuration file or using the **-x** and **-y** command-line parameters.

When **pbmtoppa** is properly calibrated, the center mark should be in the center of the paper. Also, the margins should be able to be as small as 1/4 inch without causing the printer to choke with

REDHAT LINUX INSTALLATION

RedHat users may find the following tip from Panayotis Vryonis <vrypan@hol.gr> helpful. The same should work for the 820 and 1000, but it hasn't been tested. Also, use the pbmraw GSDriver if you have it; it's faster.

Here is a tip to intergrate HP720C support in RedHat's printtool:

Install pbmtoppa. Copy pbmtoppa to /usr/bin.

Edit "printerdb" (in my system it is found in /usr/lib/rhs/rhs-printfilters) and append the following lines:

```
----------------------Cut here----------------------
StartEntry: DeskJet720C
GSDriver:pbm
Description:{HPDeskJet720C}
About:{ThisdriversupportstheHPDeskJet720Cinkjetprinter.Itdoesdoesnotsupportcolorprinting.IMPORTANT!Insert"-|pbm2ppa-"inthe
Resolution:{600}{600}{}
EndEntry
-----------------------------------------------------
```

Now you can add an HP720C printer just like any other, using printtool.

SEE ALSO

pbmpage, **pstopnm**, **pbm**

pnm2ppa is not part of Netpbm, but does the same things as **pbmtoppa** except it also works with color and has lots more features. See <http://sourceforge.net/projects/pnm2ppa>.

The file INSTALL-MORE in the pbmtoppa directory of the Netpbm source code contains detailed instructions on setting up a system to use pbmtoppa to allow convenient printing on HP PPA printers. It was written by Michael Buehlmann.

For information about the PPA protocol and the separately distributed pbm2ppa program from which **pbmtoppa** was derived, see <http://www.httptech.com/ppa>.

AUTHOR

Tim Norman. Copyright (C) 1998. Licensed under GNU Public License

Manual page by Bryan Henderson, May 2000.

Table Of Contents

NAME
SYNOPSIS
DESCRIPTION
OPTIONS
CONFIGURATION FILES
EXAMPLES
CALIBRATION

REDHAT LINUX INSTALLATION
SEE ALSO
AUTHOR