Pktopbm User Manual

pktopbm

Updated: 6 August 1990
Table Of Contents

NAME

pktopbm - convert packed (PK) format font into PBM

SYNOPSIS

pktopbm pkfile[.pk] [-x width] [-y height] [-c num] pbmfile ...

DESCRIPTION

This program is part of Netpbm.

pktopbm reads a packed (PK) font file as input, and produces PBM images as output. If the filename "-" is used for any of the filenames, the standard input stream (or standard output where appropriate) will be used. If either the width or height is specified, this value will be used for all bitmaps produced. Also if one or both values are specified, the bitmap will be relocated with the hoffset and voffset given in the pkfile. The basepoint will be placed in the lower left corner of the bitmap if the bitmap is bigger than the specified size it will be truncated at the top or right.

OPTIONS

-c *num*Sets the character number of the next bitmap written to *num*.

-x *width*Sets the width of the image in columns.

-y *width*Sets the height of the image in rows.

SEE ALSO

pbmtopk, pbm

AUTHOR

Adapted from Tom Rokicki's pxtopk by Angus Duggan <ajcd@dcs.ed.ac.uk>. <bartel@informatik.tu-muenchen.de> in March 1995.

Table Of Contents

NAME
SYNOPSIS
DESCRIPTION
OPTIONS
SEE ALSO
AUTHOR